



CRB18 series relay bases










PRC36mm

IM2 insert module

Technical data

Type	CRB1851.2	CRB1851.3	CRB1851.4
Applicable model	CR18		
Rated voltage	300V		
Rated current	12A		
Contact arrangement	2CO	3CO	4CO
Accessory	PRC36mm and IM2 insert module		
Dielectric strength adjacent contact circuits	2500		
Protection level	IP20		
Mounting method	panel and 35mm rail		
Conductor cross section solid and stranded	min.0.5mm ² /max.2.5mm ²		
Conductor cross section(A.W.G)	min.20/max.14		
Stripping length	7mm		
Screw Thread	M3		
Ambient temperature(operation)	-25 °C to +85 °C		










Technical data

Type	CRB1841.2	CRB1841.3	CRB1841.4
Applicable model	CR18		
Rated voltage	300V		
Rated current	12A		
Contact arrangement	2CO	3CO	4CO
Accessory	PRC36mm and IM2 insert module		
Dielectric strength adjacent contact circuits	2500		
Protection level	IP20		
Mounting method	panel and 35mm rail		
Conductor cross section solid and stranded	min.0.5mm ² /max.2.5mm ²		
Conductor cross section(A.W.G)	min.20/max.14		
Stripping length	7mm		
Screw Thread	M3		
Ambient temperature(operation)	-25 °C to +85 °C		



PRC36mm

IM2 insert module












CRB18 series relay bases



MRC36mm










Technical data

Type	CRB1831.2	CRB1831.3	CRB1831.4
Applicable model	CR18		
Rated voltage	300V		
Rated current	10A		
Contact arrangement	2CO	3CO	4CO
Accessory	MRC36mm		
Dielectric strength adjacent contact circuits	2500		
Protection level	IP20		
Mounting method	panel and 35mm rail		
Conductor cross section solid and stranded	1.5mm ²		
Conductor cross section(A.W.G)	16		
Stripping length	7mm		
Screw Thread	M3		
Ambient temperature(operation)	-25 °C to +85 °C		



MRC36mm



Technical data

Type	CRB1830.2	CRB1830.3	CRB1830.4
Applicable model	CR18		
Rated voltage	300V		
Rated current	10A		
Contact arrangement	2CO	3CO	4CO
Accessory	MRC36mm		
Dielectric strength adjacent contact circuits	2500		
Protection level	---		
Mounting method	panel and 35mm rail		
Conductor cross section solid and stranded	1.5mm ²		
Conductor cross section(A.W.G)	16		
Stripping length	7mm		
Screw Thread	M3		
Ambient temperature(operation)	-25 °C to +85 °C		

CRB18 series relay bases



Technical data

Type	CRB1803.2	CRB1803.3	CRB1803.4
Applicable model	CR18		
Rated voltage	300V		
Rated current	10A		
Contact arrangement	2CO	3CO	4CO
Accessory	---		
Dielectric strength adjacent contact circuits	2500		
Protection level	---		
Mounting method	PCB		
Conductor cross section solid and stranded	---		
Conductor cross section(A.W.G)	---		
Stripping length	---		
Screw Thread	---		
Ambient temperature(operation)	-25°C to +85°C		

